



ND 50 de-humidifier





50 Ltrs / Day extraction capacity



Recommended Upto 5,000 to 6,000 cu. ft. indicative coverage area



Premium Brand From Singapore since 2003 in India



Digital Display to view / set humidity & temperature



Pre-filter Screen and Carbon Filter to remove harmful pollutants and germs, and keep air fresh



Silent Mode makes very less noise



High Air Flow @ 630 m3/hr for efficient and seamless performance



Extraction (30°C, 80% RH)







Extraorior (oo o, oo o rii i)	i, duy	50
Recommended Coverage (Indicative) (Home)	cu.ft.	upto 6,000
Recommended Coverage (Indicative) (Industry)	cu.ft.	upto 5,000
Power consumption, Power supply 220V-240V/50Hz	watt	530 watts Rated Power 620 watts Max. Power
Air Flow Maximum		630 m3/hr 373 cfm
Air Flow Minimum		450 m3/hr 266 cfm
Noise Level (Approx.)	db	60 dB Max. 50 dB Min.
Dimensions (W X D X H)	inches	15 x 11 x 26
Tank Capacity	l	5
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R-410a

ka

I/day

50





Empty Weight

Running Temperature

Programmable Timer











20.2

Yes

5°C - 35°C









Industries

Healthcare

Pharma

R&D

Hotel

Warehousing

Printing

Food

Museum & Art Galleries

Defense