

ND 328 de-humidifier



20 Ltrs / Day
extraction capacity



Recommended Upto 2500-3000 cu.ft
indicative coverage area



Premium Brand From Singapore
since 2003 in india



Digital Display
to view / set humidity & temperature



Semi Permanent Built In Ionizer
for fresh indoor air quality



Auto Restart
resumes operation once power comes on



Auto Resume
pre-set humidity levels maintained on power resumption



ND328

origin

novita
Singapore

Specifications

Extraction (30°C, 80% RH)	l/day	20
Recommended Coverage (Indicative) (Home)	cu.ft.	3500
Recommended Coverage (Indicative) (Industry)	cu.ft.	2500
Power consumption, Power supply 220V-240V/50Hz	watt	304
Negative Ion Density*		Up to 20 Million/cm ³
Air Flow	m ³ / hr	225
Noise Level (Approx.)		Silent
Dimensions (W X D X H)	inches	14" x 10" x 24"
Tank Capacity	l	4
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R-134a
Empty Weight	kg	13.2
Running Temperature		5°C – 35°C
Programmable Timer		Yes



* Negative Ion Density* + Negative ion density measurement is based from source emission. ≥ 20 Million/cm³

Industries



Home



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &
Art Galleries



Defense



Climatronics™
Environment, Controlled.