





ND 838 de-humidifier



30 Ltrs / Day extraction capacity



Recommended Upto 3000-3500 cu.ft indicative coverage area



Premium Brand From Singapore since 2003 in india



Digital Display to view / set humidity & temperature



Semi Permanent Built In Ionizer for fresh indoor air quality



Auto Restart resumes operation once power comes on



Auto Resume pre-set humidity levels maintained on power resumption







Extraction (30°C, 80% RH)	<i>l</i> /day	30
Recommended Coverage (Indicative) (Home)	cu.ft.	4000
Recommended Coverage (Indicative) (Industry)	cu.ft.	3000
Power consumption, Power supply 220V-240V/50Hz	watt	405
Negative Ion Density*		Up to 20 Million/cm ³
Air Flow	m³/ hr	250
Noise Level (Approx.)	db	46
Dimensions (W X D X H)	inches	16" x 11" x 25"
Tank Capacity	l	6
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R-410a
Empty Weight	kg	15.8
Running Temperature		5°C – 35°C
Programmable Timer		Yes



* Negative Ion Density* + Negative ion density measurement is based from source emission. ≥ 20 Million/cm3



Industries

























Healthcare

Pharma

R & D

Food

Museum & Art Galleries

Defense