

origin

Climatronics®
Environment. Controlled.

O⁵⁰ de-humidifier



54 Ltrs / Day
extraction capacity



Recommended Upto 5,000 to 6,000 cu. ft.
indicative coverage area



Large Tank Capacity @ 8 Ltrs
for longer dehumidification performance



Auto Restart
resumes operation once power comes on



Auto Resume
pre-set humidity levels maintained on power resumption



High Air Flow
@ 360 m³/hr



Built In Ionizer
for fresh indoor air quality



Specifications

O⁵⁰

Extraction (l/24hr) (30°C, 80% RH)	l/24hr	54
Recommended Coverage for dehumidification (Indicative) (Home)		6,000 cu. ft.
Recommended Coverage for dehumidification (Indicative) (Industry)		5,000 cu. ft.
Power consumption, Power supply 220V-240V/50Hz	watts	695
Air Flow	m ³ /hr	360
Dimensions (W X D X H)	Inches	17" x 13" x 27"
Tank Capacity	litres	8
Compressor		Panasonic
Empty Weight	kgs	24
Running Temperature		5°C – 35°C
Programmable Timer		Yes
Humidity Setting		Electronic
Auto Restart		Yes
Auto Resume		Yes

origin


Climatronics®
 Environment. Controlled.



Industries



Home



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &



Defense