

de-humidifier

AD 680 Robust De-humidification



76.5 Ltrs / Day extraction capacity
recommended upto 8500 cu.ft



Made in Germany
since 1990



Blue Dry Technology
most energy efficient dehumidification @ 1130 watts



Easy-To-Use Electronic eDRY
displays RH level, kWh and operating hours



Optimum Dehumidifying Performance
high air flow at 750 m³/ hr



Dependable & Durable
modular metal body



AD 680

Specifications

Extraction (30°C, 80% RH)	l/day	76.5
De-humidifying performance / power consumption at **		
30°C / 80% RH	l/day	76.5 / 1130 watts
20°C / 60% RH	l/day	35 / 790 watts
15°C / 70% RH	l/day	27.5 / 710 watts
Recommended Coverage (Indicative)*	cu.ft.	8500
Max. power consumption, Power supply 230V/50 Hz	watts	1130
Air circulation rate	m³/h	750
Noise level (Approx.)	db	65
Dimensions (W X D X H)	inches	24" x 21" x 39"
Tank capacity		14l or condensate drainage
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R454C
Weight	kgs	45
Working temperature range		5°C – 34°C



Industries



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &
Art Galleries



Defense