

ECOR^{PRO}

DH3500 INOX DryFan


Stainless Steel Desiccant Dehumidifier



Light
Weight



Low Power
Consumption



4 Hole
Dehumidifier



Low
Maintenance



Perfect for
all Weather


Climatronics[®]
Environment, Controlled.

Authorized Representative for **Indian Subcontinent**
Climatronics Technologies Pvt. Ltd.
Reach Us : **+91 9152 002 004**
Email Us : **info@climatronics.in**
www.climatronics.in



DH3500 INOX DryFan

Stainless Steel Desiccant Dehumidifier

Volatge (V) (50Hz)	230V
Stainless Steel Version Available	Inox Version 316 Stainless Steel
Standard Construction	Mild Steel Epoxy Finish
Three or Four Hole Technology (Four Hole For pressure neutral drying capability)	Four - 2 internal Motor
3m noise test (1m test)db high setting	58db
Dry Air Volume(m3/hr)	380
Regen Air Volume Fan (m3/hr)	175
Total Air Flow (m3/hr)	555
Power Consumption Max(watts)	1500
Capability at 20°C 60% RH (Litres/day)	35
Litres per hour	1.46
Watts to Extract 1litre of water (W/hr/Litre) at 20°C 60% RH	1029
On Four Nylon Feet	Yes
Run Counter	Yes
Ammeter	Yes
Easy Access to Filter	Yes
External Humidistat	No (additional Part)
Internal Humidistat	No
Run Time Counter	Yes
Filters	2 x Reticulated Foam
Approval	CE
Weight(kg)	20.5
Power Cord Length (meters)	5
Plug Type	Industrial IP44
Dimensions(mm)	Dimensions(mm)
Width including Handles	500
Height	345
Depth	352
Volume(cubic meters)	0.068
Folding Carrying Handle	No
2X carrying handle protecting falanges	Yes
Ducting Included	No
Process inlet(mm)	1 X 125mm (Can be changed to 1.2 or 3 X 50mm with EPJ50 Connector)
process Outlet(mm)	1 X 125mm (Can be changed to 1.2 or 3 X 50mm with EPJ50 Connector)
Reactivation Inlet (mm)	80
Reactivation Outlet(mm)	80



Front View



Rear View



Top View



This is a 4-Hole dehumidifier meaning that there are 2 separate fans inside. One for the Process-Air (Air that needs to be dried) and the Regen Air that is used to purge the wheel of moistures and is then vented away

Easy Access to Filters

