

origin



**introducing
origin dehumidifier
ceiling & wall mounted**

oc 168 Ceiling Dehumidifier



Quiet Operation

adopts low noise centrifugal fan, with the features of a large air flow



Intelligent Humidity Controls

set the humidity and view it on a large display panel



Maintain Easily

maintenance of the ceiling dehumidifier can be carried out on the side of the ceiling dehumidifier



Reliable Water Pump

discharges water upto 1.20* meters



Quick Defrost

hot gas bypass



oc 168

Specifications

Extraction (30oC RH80%)	l/day	168
(27oC RH60%)	l/day	115
Recommended Coverage (Indicative)*	cu.ft. cu.mt.	17,000 481
Power consumption Power Supply 380 V / 50 Hz	watts	2600
Air Flow (Low Fan Speed High Fan Speed)	m³/h	1500
Noise level (Approx.)	db(A)	60
Dimensions (W X D X H)	inches	43 x 33 x 24
Trap Door Dimesions (Width X Depth)	inches	61 x 63
Water Pump	Condensate Drainage With Water Pump*	
IP Rating	IP×4	
Compressor	Rotary	
Refrigerant	R410A	
Net Weight	kgs	110.0
Working temperature	5°C - 38°C	
Timer	1 ~ 24h	



Industries

- 
 Healthcare
- 
 Pharma
- 
 R & D
- 
 Hotel
- 
 Warehousing
- 
 Printing
- 
 Food
- 
 Museum &
 Art Galleries
- 
 Defense

oc 168 Model Drawings

