

origin


Climatronics®
Environment, Controlled.

o100p built to perform



100 Liters per Day
extraction capacity



Recommended upto 10,000 cu.ft.
indicative coverage area



Anti-corrosive Body
roto molded housing for robust handling



Led Display and Electronic Control
precise operation



Water Pump
dispenses condensate up to 15ft



Higher Air Flow @ 1,000 m3/hr
for consistent and low levels of RH



o100p

Extraction (l/24hr) (30°C, 80% RH)	l/24 hr	100
Recommended Coverage (Indicative)(Industry)	cu.ft. cu.mt.	Upto 10,000 283
Power consumption, Voltage 220V-240V/50Hz	watts	1,145
Air Flow		1,000 m3/hr 591 cfm
Noise Level (Approx.)	db	60
Dimensions (W X D X H)	inches	24 x 24 x 34
Tank Capacity		Condensate drainage with water pump
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R-410a
Empty Weight	kg	56
Running Temperature		5°C – 35°C
Auto Restart Auto Resume		Available
Switch Off Timer		No
Programmable On Off Timer		Optional



Handle and
Ducting Option



Wheels for
easy mobility



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food

Museum &
Art Galleries

Defense