

origin

Climatronics®  
Environment. Controlled.

## O35p built to perform



35 Ltrs / day  
extraction capacity



Recommended up to 3,500 cu. ft.  
indicative coverage area



Anti-corrosive Body  
roto molded housing for robust handling



Led Display and Electronic Control  
precise operation



Water Pump  
dispenses condensate up to 15ft



Higher Air Flow @ 330 m<sup>3</sup>/hr  
for consistent and low levels of RH



## O35p

Extraction (I/24hr) (30°C, 80% RH)	I/24 hr	35
Recommended Coverage (Indicative)(Industry)	cu.ft.   cu.mt.	Upto <b>3,500   99</b>
Power consumption, Voltage 220V-240V/50Hz	watts	520
Air Flow		330 m <sup>3</sup> / hr   <b>195 cfm</b>
Noise Level (Approx.)	db	50
Dimensions (W X D X H)	inches	12" x 15" x 20"
Tank Capacity		Condensate drainage with water pump
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R-410a
Empty Weight	kg	33.5
Running Temperature		5°C – 35°C
Auto Restart   Auto Resume		Available
Switch Off Timer		No
Programmable On Off Timer		Optional



Digital display

Wheels for  
easy mobility

Healthcare



Pharma



R &amp; D



Hotel



Warehousing



Printing



Food

Museum &  
Art Galleries

Defense