

O53p built to perform



53 Ltrs / day
extraction capacity



Recommended upto 5000 cu.ft
indicative coverage area



Anti-corrosive Body
roto molded housing for robust handling



Led Display and Electronic Control
precise operation



Water Pump
dispenses condensate up to 15ft



Higher Air Flow @ 420 m³/hr
for consistent and low levels of RH





Ductable Option
air outlet can be ducted for focused drying



Big Wheels and Big Metal Handle
to ensure optimum on-site mobility

O53p

Specifications

Extraction (l/24hr) (30°C, 80% RH)	l/24 hr	53
Recommended Coverage (Indicative)(Industry)	cu.ft. cu.mt.	Upto 5000 Upto 142
Power consumption, Voltage 220V-240V/50Hz	watts	635
Air Flow		420 m ³ / hr 247 cfm
Noise Level (Approx.)	db	55
Dimensions (W X D X H)	inches	20" x 17" x 28"
Tank Capacity		Condensate drainage with water pump
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R-410a
Empty Weight	kg	33.5
Running Temperature		5°C – 35°C
Auto Restart Auto Resume		Available
Switch Off Timer		No
Programmable On Off Timer		Optional

Industries



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &
Art Galleries



Defense