

## Origin OS200 Industrial De-humidifier



200 ltrs/day  
extraction capacity



Recommended upto 20,000 cu.ft. | 566 cu.mt.  
indicative coverage area



Higher Air Flow @ 1,800 m<sup>3</sup>/hr  
for consistent and low levels of RH



Easy Mobility  
with castors



Condensate drainage  
Continuous drainage for uninterrupted performance



Extraction (l/24hr) (30°C, 80% RH)	l/24 hr	200
Recommended Coverage (Indicative)(Industry)	cu.ft.   cu.mt	upto 20,000   566
Dimensions	inches	30 x 19 x 63 -- (w x d x h)
Rated Power	watts	2,400   Max current. 15 A
Drainage		Continuous Drainage
Air Flow	m <sup>3</sup> /hr	1,800
Refrigerant		R410A / 1.5 kgs
Max. Suction and Discharge Pressure		2.5 MPa and 4.5 MPa respectively
Noise Level (approx.)		63 dB
Weight	kgs	120 kgs
Running Temperature		5°C to 35°C

**Also with:**

- 1.Electrical protection - under / excess voltage protection
- 2.Connectivity - Modbus



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &  
Art Galleries



Defense