



## O8€ value performance



105 Ltrs / day  
extraction capacity @ 30°C, 80% RH



Recommended upto 10000 cu.ft  
indicative coverage area



Anti-corrosive coils  
long lasting dehumidification



Led Display and Electronic Control  
precise operation



Continuous Drainage  
for seamless performance



Higher Air Flow @ 520 m<sup>3</sup>/hr  
for consistent and low levels of RH

Least RH possible  
is 40%





Extraction (l/24hr) (30°C, 80% RH)	l/24 hr	105
Recommended Coverage (Indicative)(Industry)	cu.ft.	Upto 10000
Power consumption, Voltage 220V-240V/50Hz	watts	1160
Air Flow		520 m <sup>3</sup> /hr
Noise Level (Approx.)	db	60
Dimensions (W X D X H)	inches	22 x 17 x 39
Tank Capacity		Condensate drainage with water
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R-410a
Empty Weight	kg	47
Running Temperature		5°C – 35°C
Auto Restart   Auto Resume		Available
Switch Off Timer		Yes
Programmable On Off Timer		Optional



Healthcare



Pharma



R &amp; D



Hotel



Warehousing



Printing



Food

Museum &  
Art Galleries

Defense

origin



Climatronics®

Environment, Controlled.

